



WALLCOLMONOY
HI TEMP BRAZING ALLOYS

NICROBRAZNEWS

SEPTEMBER 2020

Selecting Stop-Off™

Lydia Lee, BSE, M. Eng, MBA, Wall Colmonoy, Madison Heights, MI

Nicrobraz® Stop-Off™ materials aid in brazing and heat treating operations by preventing unwanted filler metal flow and the accidental fusing together of parts

Nicrobraz® Stop-Off™ materials were developed by Wall Colmonoy following the invention of Nicrobraz®, the nickel-based filler metal used in hydrogen atmosphere furnace, also pioneered by Wall Colmonoy.

Nicrobraz® Stop-Off™ materials are used successfully in brazing, in controlled-atmosphere furnaces, with flux and torches, and in molten-salt dip brazing of aluminum.

We are often asked which Nicrocraft® Stop-Off™ product best fits their application. Most likely, all of them work, but some may be more suitable than others.

Here are some tips on selecting Stop-Off™.






WALLCOLMONOY
HI TEMP BRAZING ALLOYS

NICROBRAZNEWS

White, Red and Blue Stop-Off™

Act as parting compounds, designed to prevent mating surfaces from being brazed together. They effectively prevent the flow of filler metal into unwanted areas.




White Stop-Off™ brushed onto bracket

Easiest to Remove White Stop-Off™

Acting as a parting compound to prevent accidental brazing of touching surfaces during furnace brazing, Microbraz® White Stop-Off™ can be applied by brushing, dipping, spraying, or with a syringe to small areas. After brazing, the remaining Stop-Off™ material can be easily brushed or wiped away.

Forms: Type I, Type II, Powder (used alone or with Microbraz® Cement)



Red Stop-Off™ applied to small holes on an ultra-cell

For Hard to Reach Internal Holes, Fine Threads, Wire Screens, or Parts with Fine Details Red Stop-Off™

Microbraz® Red Stop-Off™, originally designed for a NASA application, is 100% chemically soluble. This assures complete removal of any remaining residue in small internal holes, fine threads, or wire screens, and similar delicate details where all traces of Stop-Off™ material must be removed following brazing.

Form: Type II



Blue Stop-Off™ brushed onto surface part

For Use on Reactive Base Metals Blue Stop-Off™

Microbraz® Blue Stop-Off™ is formulated to work with reactive base metals, such as titanium and zirconium, and on super alloys, in extremely high temperature and ultra-high vacuum furnace atmosphere.

Form: Type II

Green, Yellow and Orange Stop-Off™

Surface-active materials that prevent high temperature molten filler metal from bonding to a protected surface, either by penetration or, by flowing under the Stop-Off™.



Green Stop-Off™ pen in use

Most Effective and Versatile Green Stop-Off™

Nicrobraz® Green Stop-Off™ is the strongest of all. It works with almost any type of base metal - except reactive metals, i.e. Ti, Zr. It can be used with any brazing method. It is the finest surface-protection agent and provides the best assurance for protecting a metal surface from a filler metal. Besides traditional liquid form, it also has the easiest-to-use PEN form. A little hard to remove but assures protection.

Forms: Type I, Type II, Felt-tip Pen




Yellow Stop-Off™ for Torch Brazing
image source: AWS Brazing Handbook P. 238

For Open Air and Furnace Brazing Yellow Stop-Off™

Nicrobraz® Yellow Stop-Off™ can be used not only for furnace brazing, but also for open-air torch brazing. This is typically used along side Nicrobraz® LM Rod. When a heavy layer of flux is being used, apply Nicrobraz® Yellow Stop-Off™ as much as possible.

Form: Type II



Orange Stop-Off™ brushed on vane segment

For Use in High Vacuum Furnaces and for Super-Plastic Forming Operation Orange Stop-Off™

Nicrobraz® Orange Stop-Off™, as well as Blue Stop-Off™, work effectively as a high-temperature lubricant and prevent damage to surfaces in contact and subject to movement in super-plastic forming operation.

Forms: Type I



WALLCOLMONOY
HI TEMP BRAZING ALLOYS

NICROBRAZNEWS

Notes on Type I and Type II

Type I

The solvent-based Type I materials are flammable, and should be handled as such. Normal caution should be exercised in their use. They should only be used in well-ventilated areas. Use if there is a chance of oil on the surface from the shop air. Type I is much thinner than Type II. Generally has a better bond to the base metal surface after application.

Type II

The water-based Type II products may be preferable, since they have no objectionable smell and are not flammable. (Read the material safety data sheet, before use, for further instructions on using and storing these materials.) Make sure the surfaces are clean and oil free.

For more information, please contact:

WORLD HEADQUARTERS

WALL COLMONOY CORP. (USA)

101 W. Girard

Madison Heights, MI 48071

Tel: 248-585-6400

Fax: 248-585-7960

Email: wcc@wallcolmonoy.com

EUROPEAN HEADQUARTERS

WALL COLMONOY LTD. (UK)

Alloy Industrial Estate

Pontardawe Swansea SA8 4HL

Tel: +44 (0) 1792 862287

Fax: +44 (0) 1792 860687

Email: alloyproductsales@wallcolmonoy.co.uk

About Wall Colmonoy and Brazing

Wall Colmonoy joins parts for high-temperature and corrosion applications using Nicrobraz®, Niferobraz®, and CuBraz™ brazing filler metals and brazing aids.

The pioneer of high-temperature brazing, Wall Colmonoy's expert brazing engineer, Bob Peaslee, invented a new brazing technology involving nickel-based filler metals and hydrogen atmosphere furnaces in 1950. As a result, the new filler metal, Nicrobraz®, was created.

Today, Nicrobraz®, Niferobraz®, and CuBraz™ brazing filler metals are used in a variety of industries including aerospace, oil & gas, steel, energy, food, automotive, rail and defense, meeting AWS, AMS, G.E., Honeywell, Pratt & Whitney and Rolls-Royce specifications. Nicrobraz products are available as powder, paste, transfer tape, rods and sheets in a full range of sizes and specifications. Wall Colmonoy also custom formulates brazing filler metals to meet customer specific requirements.

Aerobraz Engineered Technologies, a division of Wall Colmonoy, manufactures engineered components and provides technological solutions for the aerospace, energy, defense and transportation industries. This division meets aerospace quality standards in applications using the process of brazing, surfacing, welding, thermal processing, fabricating, machining and overhauling. Aerobraz Engineered Technologies has the engineering expertise to take concepts from design to prototype to production.

Copyright © 2020 by Wall Colmonoy Corporation. All rights reserved.

No part of this work may be published, translated or reproduced in any form or by any means, or incorporated into any information retrieval system, without the written permission of the copyright holder. Permission requests should be addressed to: Marketing Communications, marketing@wallcolmonoy.com

Disclaimer

Although the information presented in this work is believed to be reliable, this work is published with the understanding that Wall Colmonoy Corporation and the authors are supplying general information and are not attempting to render or provide engineering or professional services. Neither Wall Colmonoy Corporation nor any of its employees make any warrant, guarantee, or representation, whether expressed or implied, with respect to the accuracy, completeness or usefulness of any information, product, process or apparatus discussed in this work; and neither Wall Colmonoy Corporation nor any of its employees shall be liable for any losses or damages with respect to or resulting from the use of, or the inability to use, any information, product, process or apparatus discussed in this work.